

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 June 2005 (09.06.2005)


PCT

(10) International Publication Number
WO 2005/052433 A1

- (51) International Patent Classification: **F16L 47/16** (74) Agent: **KOLSTER OY AB**; Iso Roobertinkatu 23, P.O. Box 148, FI-00121 Helsinki (FI).
- (21) International Application Number: PCT/PT2004/000714 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 25 November 2004 (25.11.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 20031736 27 November 2003 (27.11.2003) FI
- (71) Applicant (for all designated States except US): **UPONOR INNOVATION AB** [SE/SE]; Industrivägen, S-513 81 Fristad (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **SMAHL, Jarmo** [FI/FI]; Satukaari 10, FI-15550 Nastola (FI).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PIPE FITTING



(57) Abstract: A pipe fitting is made of plastic, such as polysulphone PSU or polyphenylsul-phone PPSU. At least one end of the pipe fitting (1) comprises an external thread (2) for connecting the pipe fitting (1) to a mounting element, such as a pipe or a mounting piece, e.g. a tap. The thread (2) comprises a ridge (3). Between the ridges (3) there is a continuous helical groove (4). On the bottom of the groove (4) between the ridges (3) of the thread (2) there are protrusions (5).

WO 2005/052433 A1

**Declaration under Rule 4.17:**

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ,*

BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

PIPE FITTING

BACKGROUND OF THE INVENTION

[0001] The invention relates to a pipe fitting, which is made of plastic, intended to act as a connection piece to join at least two mounting elements, and at least one end of which comprises a thread for connecting the pipe fitting and the mounting element to each other by means of a threaded connection.

[0002] A pipe fitting is used as a connection piece to connect, for example, a mounting piece, such as a tap, to a pipe or as a connection piece to connect a pipe to another pipe or to another similar object. Previously, mainly metallic pipe fittings were used. However, material and manufacturing costs of metallic pipe fittings are quite high. In addition, to make the connections in the metallic pipe fittings tight requires remarkable expertise. Pipe fittings can also be made of plastic. Also when plastic pipe fittings are used, it is necessary to have a good knowledge of how to make the connections tight.

BRIEF DESCRIPTION OF THE INVENTION

[0003] It is an object of the invention to provide a new and improved pipe fitting.

[0004] The pipe fitting of claim 1 is characterized in that on the bottom of a groove between ridges of the thread there are protrusions.

[0005] The pipe fitting is preferably made of plastic and at least its one end comprises a thread for connecting the pipe fitting to the mounting element. If the groove between the ridges of the thread is provided with protrusions, a seal to be arranged onto the threads can be fixed very firmly to its place when the mounting element and the pipe fitting are connected to each other by means of a threaded connection. Also when the threaded connection is opened, the seal remains quite well in its place. The protrusions on the bottom of the groove also make the connection tighter so that no fluid can flow along the groove of the threads. Consequently, the connections are made considerably tighter. If the threaded end of the pipe fitting is provided with an unthreaded section in the starting end of the pipe fitting, this unthreaded section acts as a guide surface for the mounting element to be arranged in the pipe fitting, whereupon the mounting element provided with a thread suitably fits into the threads of the pipe fitting. Thus, the unthreaded part acts as a guide element which hinders the mounting element from being in an inclined

position with respect to the pipe fitting, which inclined position could damage the threads of the pipe fitting and/or mounting element. Thus, the tightness of the connection can also be improved by means of the unthreaded part, since the threads remain undamaged and the threaded connection can be implemented easily and properly.

BRIEF DESCRIPTION OF THE FIGURES

[0006] The invention will be described in more detail in the attached drawing, in which

Figure 1 schematically shows a side view of a pipe fitting, and
Figure 2 shows a cross-section of the pipe fitting of Figure 1, taken along the line A – A of Figure 1.

DETAILED DESCRIPTION OF THE INVENTION

[0007] Figure 1 shows a pipe fitting 1, i.e. a connection piece. The pipe fitting 1 is used between two or more mounting elements to connect them. The first mounting element can be, for example, a pipe or a mounting piece, such as a tap or the like, and the second mounting element can be a pipe, for instance. The pipe fitting 1 can be a bend, as shown in Figure 1, or the pipe fitting 1 can be a straight piece, for example. Furthermore, the pipe fitting 1 can be a T-piece, which means that the pipe fitting 1 is used to connect three different mounting elements to each other. Thus, the appearance and purpose of use of the pipe fitting 1 can vary within very broad limits.

[0008] The pipe fitting 1 is made of plastic, such as polyethylene PE, polypropylene PP, cross-linked polyolefin plastic, such as cross-linked polyethylene PEX, polyamide PA, polysulphone PSU, polyphenylsulphone PPSU or polyvinylidene fluoride PVDF. If desired, additives, such as a reinforcement, e.g. glass fibre, can be mixed into the plastic.

[0009] At the first end of the pipe fitting 1 there is an external thread 2. The thread 2 comprises a ridge 3. Between the ridges 3 there is a continuous helical groove 4.

[0010] On the bottom of the groove 4 there are protrusions 5. The pipe fitting 1 is connected by means of the thread 2 to the mounting element provided with an internal thread. In Figure 1, the mounting element is shown symbolically by means of a broken line. A seal is arranged in the threaded connection between the external thread 2 of the pipe fitting 1 and the internal thread of the mounting element in order to secure the tightness of the threaded

connection. Due to the protrusions 5, the seal 7 remains in its place at the thread 2 when the threaded connection is implemented. Furthermore, when the connection is opened, the protrusions 5 keep the seal 7 in its place. The protrusions 5 also prevent the leaking of the threaded connection by hindering the fluid from flowing along the bottom of the groove 4.

[0011] For example, a sealing strip, sealing tape, hemp or some other sealing can be used as a seal in a manner known per se. If the pipe fitting 1 is made of polyphenylsulphone PPSU, a sealing material with a trade name Loctite 5061 has proven to be a good seal. The seal 7 is preferably arranged in connection with the pipe fitting 1 already during the manufacture of the pipe fitting 1 at the factory. Thus, it is ensured that a proper kind of sealing material is used and that the seal is properly arranged in connection with the thread 2.

[0012] The protrusions 5 do not necessarily extend to the starting end of the thread 2, and thus the starting end of the groove 4 can have an even bottom. This makes it easier to implement the threaded connection and the threads are set against each other easily. In Figure 1, the protrusions 5 are arranged in the same line with each other in the successive grooves, whereby the protrusions 5 form axial ribs. Thus, the manufacture of the pipe fitting 1 by means of injection moulding, for instance, is as simple as possible and it is easy to form an injection mould, for example. For the sealing effect, however, it is not necessary that the protrusions in the successive grooves are in the same line with each other but they may even be arranged randomly around the pipe fitting 1. On the other hand, the protrusions 5 can be arranged to form the ribs at an angle diverging from the axial direction.

[0013] There can be, for instance, 2 to 24 protrusions 5 that are arranged at one point around the circumference, i.e. at a distance covered by one pitch. Typically, there are 4 to 8 protrusions at one point around the circumference. In the case of Figures 1 and 2, there are eight protrusions 5 around the circumference.

[0014] The height of the protrusion 5 depends on the diameter of the pipe fitting 1 and the height of the ridge 3. The height of the protrusion 5 is typically 10 to 50% of the height of the ridge 3, for instance. The height of the protrusion 5 can vary between 0.2 and 2 mm, for example. The diameter D of the pipe fitting can vary between 10 and 30 mm, for example.

[0015] At the first end of the pipe fitting 1 provided with the thread 2 there can be an unthreaded section 6 in the starting end before the thread 2. The unthreaded section 6 forms a guide surface, which guides the pipe fitting 1 and the mounting element to be connected thereto with respect to one another in such a manner they have parallel middle axes. Consequently, the threads are set precisely against each other and it is easy to implement a threaded connection and the threads will not get damaged. Furthermore, the unthreaded section 6 provides the advantage that at the point where the thread 2 starts, the wall of the pipe fitting 1 has a greater strength than at the very end of the pipe fitting. At the thread 2 the wall is not as elastic as at the end of the pipe fitting and due to the mould technique, the wall of the end part of the injection mould section must be made slightly thinner so that the section of the mould to be arranged inside the casting can be separated after the casting. Due to the unthreaded section 6, the thread 2 starts where the wall is a bit thicker than at the end of the pipe fitting 1. Consequently, it is easier to keep the thread 2 unchanged and the connection becomes very tight.

[0016] Typically, the length l of the unthreaded section equals to the pitch of ca. 1 to 2 threads. Preferably, the ratio of the length l of the unthreaded section 6 to the diameter D of the pipe fitting 1 is greater than 1:6. Particularly preferably the ratio of the length l of the unthreaded section 6 to the diameter D of the pipe fitting 1 is greater than 1:4.

[0017] The drawings and the related description are only intended to illustrate the idea of the invention. In its details, the invention can vary within the scope of the claims. The pipe fitting 1 can have any single feature described above either individually or in combination with other features. For example, the pipe fitting 1 can have the unthreaded part 6 before the thread 2, but it need not necessarily have protrusions 5 on the bottom of the groove 4 then. A very good tightness is provided in this case, too. If desired, the protrusions 5 can be made of a softer material than the rest of the pipe fitting. Thus, when the threaded connection is implemented, the protrusions are shaped because of the pressing of the threads of the mounting element. Furthermore, the protrusions can, if desired, also be arranged in a position diverging from the axial direction, i.e. obliquely in either direction. In this case, the protrusions wedge the sealing material towards the ridge, providing a better tightness. Furthermore, the protrusions 5 need not necessarily extend from one ridge to another but the seal remains in its place also when at least a part of the distance

5

between the ridges is uneven. The upper surface of the protrusions 5 can be straight, as shown in Figure 1, or the upper surface of the protrusions 5 can be convex or concave, for example.

CLAIMS

1. A pipe fitting, which is made of plastic, intended to act as a connection piece to join at least two mounting elements, and at least one end of which comprises a thread (2) for connecting the pipe fitting (1) and the mounting element to each other by means of a threaded connection, **characterized** in that on the bottom of a groove (4) between ridges (3) of the thread (2) there are protrusions (5).
2. A pipe fitting as claimed in claim 1, **characterized** in that the height of the protrusions (5) is 10 to 50% of the height of the ridge (3).
3. A pipe fitting as claimed in claim 1 or 2, **characterized** in that at the starting end of the thread (2) the bottom of the groove (4) does not comprise protrusions at least at the distance of one pitch.
4. A pipe fitting as claimed in any one of the preceding claims, **characterized** in that the protrusions (5) are arranged in the successive grooves (4) in such a manner that the protrusions (5) form ribs.
5. A pipe fitting as claimed in claim 4, **characterized** in that the protrusions (5) are arranged in the same line with each other in the axial direction such that they form axial ribs.
6. A pipe fitting as claimed in any one of the preceding claims, **characterized** in that the thread (2) is arranged at a distance from the end of the pipe fitting (1) in such a manner that the end of the pipe section (1) comprises an unthreaded section (6) acting as a guide surface.
7. A pipe fitting as claimed in claim 6, **characterized** in that the ratio of the length l of the unthreaded section (6) to the diameter D of the pipe fitting (1) is greater than 1:6.
8. A pipe fitting as claimed in any one of the preceding claims, **characterized** in that there are 2 to 24 protrusions (5) at one point around the circumference of the pipe fitting (1).
9. A pipe fitting as claimed in any one of the preceding claims, **characterized** in that the upper surface of the protrusion (5) is straight.
10. A pipe fitting, which is made of plastic, intended to act as a connection piece to join at least two mounting elements, and at least one end of which comprises a thread (2) for connecting the pipe fitting (1) and the mounting element to each other by means of a threaded connection, **characterized** in that the thread (2) is arranged at a distance from the end of the

pipe fitting (1) in such a manner that the end of the pipe fitting (1) comprises an unthreaded section (6) acting as a guide surface.

11. A pipe fitting as claimed in claim 10, **characterized** in that the ratio of the length l of the unthreaded section (6) to the diameter D of the pipe fitting is greater than 1:6.

12. A pipe fitting as claimed in claim 10, **characterized** in that the ratio of the length l of the unthreaded section (6) to the diameter D of the pipe fitting (1) is greater than 1:4.

13. A pipe fitting as claimed in any one of claims 10 to 12, **characterized** in that on the bottom of a groove (4) between ridges (3) of the thread (2) there are protrusions (5).

14. A pipe fitting as claimed in claim 13, **characterized** in that at the starting end of the thread (2) the bottom of the groove (4) does not comprise protrusions at least at the distance of one pitch.

15. A pipe fitting as claimed in claim 13 or 14, **characterized** in that the protrusions (5) are arranged in the successive grooves (4) in such a manner that the protrusions (5) form ribs.

16. A pipe fitting as claimed in claim 15, **characterized** in that the protrusions (5) are arranged in the same line with each other in the axial direction such that they form axial ribs.




FIG. 1




FIG. 2

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 2004/000714

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: F16L 47/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: F16L, F16B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3502355 A (H.W. DEMLER, SR. ET AL), 24 March 1970 (24.03.1970), column 4, line 52 - column 5, line 5, figures 7-10 --	1
Y	AU 35181 A (JOHN BRIAN O'HAIR ET AL), 3 May 1973 (03.05.1973), figure A --	1
Y	US 2484644 A (O.J. POUPITCH), 11 October 1949 (11.10.1949), figures 1-3 --	1
Y	US 3856065 A (GEHRING), 24 December 1974 (24.12.1974), figures 1-2 --	1

☒ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 March 2005

Date of mailing of the international search report

11-03-2005

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Inger Löfving / JA A

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 2004/000714

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4154466 A (SIMMONS), 15 May 1979 (15.05.1979), column 3, line 32 - column 4, line 22, figures 2-3 -- -----	10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/FI 2004/000714

US	3502355	A	24/03/1970	NONE		
AU	35181	A	03/05/1973	NONE		
US	2484644	A	11/10/1949	NONE		
US	3856065	A	24/12/1974	NONE		
US	4154466	A	15/05/1979	AU	514698 B	19/02/1981
				AU	3206977 A	05/07/1979
				CA	1082247 A	22/07/1980
				CA	1102847 A	09/06/1981
				CA	1102848 A	09/06/1981
				CA	1118469 A	16/02/1982
				FR	2376354 A,B	28/07/1978
				GB	1600608 A	21/10/1981
				GB	1600609 A	21/10/1981
				GB	1600610 A	21/10/1981
				IE	46637 B	10/08/1983
				IE	46638 B	10/08/1983
				IE	46639 B	10/08/1983
				IE	772648 L	03/07/1978
				IE	812783 L	03/07/1978
				IE	812784 L	03/07/1978
				JP	53089021 A	05/08/1978
				MY	45986 A	31/12/1986
				MY	46086 A	31/12/1986
				MY	97685 A	31/12/1985
				NL	185238 B,C	18/09/1989
				NL	7713919 A	05/07/1978
				NO	161820 B,C	19/06/1989
				NO	774200 A	04/07/1978
				SG	84984 G	07/06/1985
				SG	85084 G	07/06/1985
				SG	85284 G	07/06/1985
				US	RE31123 E	11/01/1983